

Fast Exit & Emergency Luminaires

FLED

The FASTLED slimline 3W LED wall or ceiling mounted all-in-one maintained exit is designed for low maintenance and low power consumption.

Features and Benefits

- Bright and consistent LED light distribution
- Long life LED operation - 50,000 hours continuous
- Low power consumption
- Wall or ceiling mountable
- Complete with all variations of running man decals
- Premium 70°C high temperature NiCad batteries
- Designed and manufactured in accordance to AS/NZS 2293



FLED		
Input	Operating Voltage	230V
	Frequency	50Hz
Output	Light Source	50,000 hour LEDs
	Function	Maintained
	Power Consumption (LEDs)	3W
Battery	Type	High Temperature Nickel Cadmium
	Charger	Intelligent Dual Rate Charger
	Protection	Overcharge and low voltage disconnect
	Emergency Runtime	2 hours*
Physical	IP Classification	IP20
	Weight	2.0kg
	Length	375mm
	Width	70mm
	Height	230mm
	Construction	Glass filled ABS
Installation	Mounting	Wall or Ceiling
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	C0	D3.2
	C90	E2.5
	Standards	AS/NZS 2293 / EMC
Intelligence	Sentinel	No
	WiNetRF	No
Warranty	Duration	Fitting: 2 Years / Battery: 1 Year

*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
BEL - 074715	Replacement Battery for FLED

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 – D3.2 (m)	6.5	6.6	6.6	6.5
C90 – E2.5 (m)	5.6	5.8	5.8	6.0

*Refer to AS/NZ 2293 for complete spacing table.