

PREMIUM Exit and Emergency Luminaires

EZYLEDLP/WP - All-in-One Weatherproof Exit

PREMIUM Weatherproof All-in-one exit complete with all variations of running man decals. Features Sentinel Automatic Self-testing and LiFePO₄ battery technology with Battery Management System to maximise battery life. The weatherproof casing is manufactured from high impact polycarbonate to withstand the harshest environmental conditions.



LiFePO₄POWER™



Features and Benefits

- Weatherproof design with IP65 Classification
- In built Sentinel Automatic testing capability
- High output LEDs for bright consistent & efficient light distribution
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximize battery life
- Complete with all variations of the "Running Man" decal pack with a 24m viewing distance
- Over 2 hours runtime in emergency mode
- For sub-zero applications a remote box version is available upon request
- Designed and manufactured in accordance to AS/NZS 2293

EZYLEDLP/WP		
Input	Operating Voltage	230V
	Frequency	50Hz
Output	LED Array	12 x Everlight 67-21S LEDs
	Light Source	3W
	Function	Maintained
	Power Consumption (LEDs)	4W
Battery	Type	LiFePO ₄
	Charger	Variable current CV
	Protection	Charger overcharge and low voltage disconnect
	Emergency Runtime	2 hours*
Physical	IP Classification	IP65
	Weight	2kg
	Dimensions (LxHxW)	430x300x160mm
	Construction	Exit: Fire Retardant ABS V0. Weatherproof case: Polycarbonate
Installation	Mounting	Ceiling
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	C0 / C90	D3.2 / E2.5
	Standards	AS/NZS 2293 / EMC
Warranty	Duration	Fitting: 5 Years / Battery: 1 Year
Intelligence	Sentinel	In-built
	WiNetRF	Compatible

*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
BEL-31511	Replacement battery for EZYLEDLP

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 - D3.2 (m)	6.5	6.5	6.5	6.5
C90 - E2.5 (m)	5.4	5.6	5.8	5.8

*Refer to AS/NZ 2293 for complete spacing table.