

PREMIUM Exit & Emergency Luminaires

FINLP

The FINLP Magnetic Fascia LED Recessed Blade Exit combines a sleek functionality and unobtrusive design with excellent illumination.



LiFePO₄ POWER™



Features and Benefits

- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximize battery life
- Innovative magnetic screw-less fascia design
- Sleek and unobtrusive with ultra low power consumption
- In-built Sentinel automatic self-testing capability
- Excellent illumination in mains and emergency modes
- No external assembly or mounting screws
- Long life LED operation - 50,000 hours continuous
- Designed and manufactured in accordance to AS/NZS 2293

FFIN (Body only)		
Input	Operating Voltage / Frequency	230V / 50Hz
Output	Light Source	50,000 hour LEDs
	Function	Maintained / Non-Maintained / Switchable
	Power Consumption (LEDs)	2W
Battery	Type	LiFePO ₄
	Charger	Variable current CV
	Protection	Charger overcharge and low voltage disconnect
	Emergency Runtime	2 hours*
Physical	IP Classification	IP20
	Weight	3.5kg
	Dimensions (LxWxH)	415x97x235mm
	Construction	Folded sheet metal chassis, acrylic diffuser panel
Installation	Ceiling Mount	Recessed
	Ceiling Cutout	375 x 75mm
Environment	Temperature / Relative Humidity	0°C - 40°C / 0 - 95%
Conformance	C0	D6.3
	C90	C32
	C180	D12.5
	Standards	AS/NZS 2293 / EMC
Intelligence	Sentinel	In-built
	WiNetRF	Compatible
Warranty	Duration	Fitting: 5 Years / Battery: 1 Year

*Guaranteed to meet runtime requirements of AS/NZ 2293 within warranty period.

ACCESSORY	DESCRIPTION
FDS	Running Man Diffuser S/Side - No Arrow
FDA	Running Man Diffuser D/Side - Common End Arrow
31511	Replacement Battery for FINLP

*Diffuser & body sold separately.

SPACING TABLE FINLP+FDS	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 – D6.3 (m)	8.6	8.8	9.0	9.1
C90 – C32 (m)	10.0	10.7	11.3	11.8
C180 – D12.5 (m)	11.5	11.5	11.8	12.1

*Refer to AS/NZ 2293 for complete spacing table.