

PREMIUM Exit and Emergency Luminaires

MLEDLPWP Classic Weatherproof Exit

Body and Diffuser sold separately.

BARDIC has a complete range of weatherproof fittings. The 3W Classic Weatherproof fitting is manufactured from high impact polycarbonate to withstand the harshest environmental and weather conditions.

Features and Benefits

- In-built Sentinel Self-testing capability
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximise battery life
- High temperature components for extended life
- For sub-zero applications a remote box version is available upon request.
- Designed and tested in accordance to AS/NZS 2293



LiFePO₄ POWER™



MLEDLPWP (Body and Diffuser sold separately)		
Input	Operating Voltage	230V
	Frequency	50Hz
Output	Light Source	6 x 0.5W Everlight LEDs
	Function	Maintained / Non-maintained / Switched
	Power Consumption	3W
Battery	Type	LiFePO ₄
	Charger	Variable current CV
	Protection	Charger overcharge & low voltage disconnect
	Emergency Runtime	2 hours*
Physical	IP Classification	IP66
	Weight	3.0kg
	Dimensions (LxHxW)	385x185x135mm
	Construction	Glass-filled polycarbonate
Installation	Mounting	Surface - Wall
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	C0	E1.25
	C90	E1
	Standards	AS/NZS 2293 / EMC
Warranty	Duration	Fitting: 5 Years / Battery: 1 Year
Intelligence	Sentinel	In-built
	WiNetRF	Compatible

*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORIES	DESCRIPTION
RMWP1	Running man (Straight ahead) diffuser
RMWP2	Running man (Right) diffuser
RMWP3	Running man (Left) diffuser
WPA	Wall / ceiling mount clear weatherproof diffuser
31511	Replacement battery to suit MLEDLPWP

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 - E1.25 (m)	4.2	4.2	4.0	3.6
C90 - E1 (m)	3.8	3.6	3.2	3.6

*Refer to AS/NZ 2293 for complete spacing table.

*Diffuser & body sold separately.